**US Army Corps
of Engineers**
Construction Engineering
Research Laboratory

AD-A221 332

Guidelines for Running GRASS Benchmarks

by
Mark O. Johnson

DTIC
ELECTE
APR 2 5 1990
S D
D

The Geographic Resources Analysis Support
System (GRASS) is a geographic information
and image processing system originally design-
ed to serve land managers and environment
planners at Army installations. GRASS is public
domain software distributed by several public
and private organizations. Consequently, there
are many different hardware configurations
running GRASS. This guide documents current
procedures used to conduct system performance
tests (benchmarks), to provide users considering
the acquisition of the system a reliable means to
compare the many systems that run GRASS.
Relevant data that accompany benchmark re-
sults are: machine specifications; system envi-
ronment; GRASS program environment; GRASS
graphics environment; operation descriptions;
data description; and benchmark execution
notes.

90 04 23 123

REPORT DOCUMENTATION PAGE

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE February 1989	3. REPORT TYPE AND DATES COVERED Final

4. TITLE AND SUBTITLE	5. FUNDING NUMBERS
Guidelines for Running GRASS Benchmarks	ZP9:R-FED-SCS, GRASS-SCS

6. AUTHOR(S)

Johnson, Mark O.

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)	8. PERFORMING ORGANIZATION REPORT NUMBER
U.S. Army Construction Engineering Research Laboratory P.O. Box 4005 Champaign, IL 61824-4005	USACERL TM N-89/23

9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)	10. SPONSORING / MONITORING AGENCY REPORT NUMBER
USDA Soil Conservation Service (SCS) 14th Street & Independence Ave. SW. Washington, DC 20250	

11. SUPPLEMENTARY NOTES

Copies are available from the National Technical Information Service, Springfield, VA 22161.

12a. DISTRIBUTION / AVAILABILITY STATEMENT	12b. DISTRIBUTION CODE
Approved for public release; distribution is unlimited.	

13. ABSTRACT (Maximum 200 words)

The Geographic Resources Analysis Support System (GRASS) is a geographic information and image processing system originally designed to serve land managers and environment planners at Army installations. GRASS is public domain software distributed by several public and private organizations. Consequently, there are many different hardware configurations running GRASS. This guide documents current procedures used to conduct system performance tests (benchmarks), to provide users considering the acquisition of the system a reliable means to compare the many systems that run GRASS. Relevant data that accompany benchmark results are: machine specifications; system environment; GRASS program environment; GRASS graphics environment; operation descriptions; data description; and benchmark execution notes.

14. SUBJECT TERMS			15. NUMBER OF PAGES
GRASS benchmarks hardware			
			16. PRICE CODE

17. SECURITY CLASSIFICATION OF REPORT	18. SECURITY CLASSIFICATION OF THIS PAGE	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT
UNCLASSIFIED	UNCLASSIFIED	UNCLASSIFIED	SAME AS REPORT

NSN 7540-01-280-5500

Standard Form 298 (Rev. 2-89)
Prescribed by ANSI Std Z39-18
298-102

FOREWORD

GUIDELINES FOR RUNNING GRASS BENCHMARKS

Mark O. Johnson

U.S. Army Construction Engineering Research Laboratory
P.O. Box 4005
Champaign, IL. 61824-4005

ABSTRACT

The purpose of the report is to document the current procedures used to conduct system performance tests (benchmarks) for computers running the Geographic Resources Analysis Support System (GRASS).

1. Introduction

The purpose of the GRASS benchmarks is to provide would-be users with a general means of comparison between the many systems now running GRASS. This information will be used to compile and update the *GRASS Hardware Configuration Guide*[1] and will be featured in the quarterly issues of *GRASSClippings*.[2] It should be stressed that speed is not the sole factor in deciding what system best suits a user's needs. Other factors to consider include, but are not limited to, system price, cost and responsiveness of hardware and software maintenance services, system limitations, and upgrade capabilities.

2. Documenting Machine Specifications

The following information should be provided with the benchmark results to describe the system being tested. A form is provided to record this information. When completed you should send the form to the above address.

System Name

Industry name, model number, etc..

Configuration Price

List price of system configuration being tested.

Processor

What type (68030,80386,..) and how many.

Floating Point Processor

What type (68881,...) if any.

Accesion For		
NTIS CRA&I		☒
DTIC TAB		☐
Unannounced		☐
Justification		
By		
Distribution /		
Availability Codes		
Dist	Avail and / or Special	
A-1		

[1] Douglas A. Brooks, Michael E. Higgins, and Mark O. Johnson, *GRASS Hardware Configuration Guide*, ADP Report N-89/21 (U.S. Army Construction Engineering Research Laboratory [USACERL], March 1989).

[2] *GRASSClippings*, ISSN 0899-7853, published quarterly by the GRASS Inter-Agency Steering Committee.

Memory

Amount (in megabytes) of RAM memory installed.

Maximum amount (in megabytes) of RAM memory expansion possible.

Disk Brand, Size, and Access Speed

Brand name of disk (Fujitsu, Hitachi,...)

Disk size (in megabytes)

Disk access speed claimed by manufacturer (in microseconds [ms]).

Clock Speed

CPU speed in megahertz (Mhz).

Graphics System

Description of graphics system including, but not limited to, such things as industry known name, number of planes, number of buffers, number of colors supported (palette & displayable). This will be condensed to fit space available.

Screen Resolution & Size

If the full screen will be used as the graphics window specify screen resolution. If using a sub-window for graphics, specify the size (in pixels) within the sub-window.

3. Setting up System Environment for Benchmarks

The purpose of these tests is to determine what a normal user should expect in terms of response time.

The following conditions should be maintained during
testing:
- NO SYSTEM OPTIMIZING: ALL normal system daemons
and processes should be active.
- NO OTHER USERS: Be sure you are the sole user of
the system during testing. We don't want to
measure swap time between you and another user.
However the system should be in multi-user mode.
- SYSTEM SHELL: Use whatever shell (csh,sh,..) users
are normally expected to use. Most users tend to
use the csh-shell if available. Please document
your choice on the form provided.

4. Setting up GRASS Environment for Benchmarks

Enter the GRASS system, selecting **spearfish** as your location and any name you choose as the mapset. Once you have a GRASS system prompt enter the following command:

Gwindow default print

This will set the area of interest and the resolution to match those of the spearfish locations default settings. You should see a confirmation like this:

Mapset < benchmarks> in Location < spearfish>
GRASS-GRID > Gwindow default print

projection:	1 (UTM)
zone:	13
north:	4928000.00
south:	4914000.00
east:	609000.00
west:	590000.00
nsres:	100.00
ewres:	100.00
rows:	140
cols:	190

5. Setting up GRASS Graphics Environment for Benchmarks

When setting up the graphics environment, be sure your graphics window covers the entire screen. If you're running the graphics driver within a window management system (suntools,X,...) either make the graphics window fill the screen or document the size (in pixels) of the graphics window.

6. Operation Descriptions

These are the commands to be used for benchmark testing. It is assumed that no modifications have been done. Any modifications should be completely documented and returned with the benchmark results.

1) Dcell - A raster data display function involving disk I/O and
   raster output which is used to fill the computer
   graphics screen with a data layer.
2) Gstats - Program involving disk I/O and up to 4 byte integer
   operations to calculate the frequency of common
   occurrence of categories between one or more data layers.
3) Dvect - A vector display function involving disk I/O and vector
   output which is used to draw vector lines from a data
   file to the computer graphics screen.
4) Gslope.aspect - Program to create slope and aspect data layers
   from an elevation data layer involving disk I/O
   and floating point computation.

7. Data Description

The data layers geology and elevation will be used in performing tests 1,2,& 4. The geology data layer has a resolution of 100 x 100 meters. The elevation data layer has a resolution of 30 x 30 meters. DO NOT RESAMPLE the elevation data layer to fit the 100 x 100 meter window. The vector file roads will be used for the Dvect benchmark.

8. Benchmark Execution Notes

The UNIX command time will be used to measure the speed at which the program was executed. This command returns several measurements depending on the version of UNIX and the type of shell (sh or csh) being used. The tester should record the entire line returned by the time command.

9. Benchmark Execution

The following represent examples of benchmark execution for each test program.

9.1. Dcell

Mapset < benchmarks> in Location < spearfish>
GRASS-GRID > time Dcell elevation
3.3u 3.4s # :# # 15% 31+ 26k 294+ 53io 0pf+ 0w

9.2. Gstats

Mapset < benchmarks> in Location < spearfish>
GRASS-GRID > time Gstats geology elevation > gstat.out
3.3u 3.4s # :# # 15% 31+ 26k 294+ 53io 0pf+ 0w

9.3. Dvect

Mapset < benchmarks> in Location < spearfish>
GRASS-GRID > time Dvect roads
3.3u 3.4s # :# # 15% 31+ 26k 294+ 53io 0pf+ 0w

9.4. Gslope.aspect

Mapset < benchmarks> in Location < spearfish>
GRASS-GRID > time Gslope.aspect elevation= elevation slope= s.test aspect= a.test
3.3u 3.4s # :# # 15% 31+ 26k 294+ 53io 0pf+ 0w

The tester may want to remove the cell files created by Gslope.aspect (s.test, a.test) and the file created by Gstats (gstats.out).

GRASS BENCHMARK INFORMATION SHEET

System Information

   System Name

   Configuration Price

   Processor

   Floating Point Processor

   Memory

        tested system amount:
        maximum amount:

   Disk Brand, Size, and Access Speed

        Disk brand name:
        Disk size:
        Disk speed:

   Clock Speed

   Graphics System

   Screen Resolution & Size

   Shell of Choice

   Other System Information

Description of other standard system features which come with system as priced (ethernet, racksize, number of expansion slots, tape systems, manuals).

- 6 -

Benchmark Results

Mapset < benchmarks> in Location < spearfish>
GRASS-GRID > time Dcell elevation
Enter complete time results here:

Mapset < benchmarks> in Location < spearfish>
GRASS-GRID > time Gstats geology elevation > gstat.out
Enter complete time results here:

Mapset < benchmarks> in Location < spearfish>
GRASS-GRID > time Dvect roads
Enter complete time results here:

Mapset < benchmarks> in Location < spearfish>
GRASS-GRID > time Gslope.aspect elevation= elevation slope= s.test aspect= a.test
Enter complete time results here:

USACERL DISTRIBUTION

Chief of Engineers
ATTN: CEIM-SL (2)
ATTN: CECC-P
ATTN: CECW
ATTN: CECW-O
ATTN: CECW-P
ATTN: CECW-RE
ATTN: CECW-RR
ATTN: CEMP
ATTN: CEMP-C
ATTN: CEMP-E
ATTN: CERD
ATTN: CERD-L
ATTN: CERD-C
ATTN: CERD-M
ATTN: CERM
ATTN: DAEN-ZCE
ATTN: DAEN-ZCI
ATTN: DAEN-ZCM
ATTN: DAEN-ZCZ

CEHSC ATTN: CEHSC-ZC 22060
ATTN: DET III 79906

Allied Command Europe (ACE)
ATTN: ACSGEB 09011
ATTN: SHIIB/Engineer 09055
ATTN: AEUES 09081

US Military Academy 10966
ATTN: Facilities Engineer
ATTN: Dept of Geography &
Computer Science
ATTN: MAEN-A

FORSCOM
FORSCOM Engineer, ATTN: Spt Det.
ATTN: Facilities Engineer (27)

HSC
Ft. Sam Houston AMC 78234
ATTN: HSLO-F
Fitzsimons AMC 80045
ATTN: HSHG-DEH
Walter Reed AMC 20307
ATTN: Facilities Engineer

INSCOM - Ch, Instl. Div.
Arlington Hall Station 22212 (4)
ATTN: Facilities Engineer
Vint Hill Farms Station 22186
ATTN: IAV-DEH

TRADOC
HQ, TRADOC, ATTN: ATEN-DEH 23651
ATTN: DEH (18)

Fort Belvoir, VA 22060
ATTN: Water Resource Center
ATTN: Engr Studies Center
ATTN: Engr Topographic Lab
ATTN: ATZA-TE-SW
ATTN: STRBE-BLURE
ATTN: CEHSC-FN 22060-5580

CECRL, ATTN: Library 03755

WES, ATTN: Library 3918

HQ, XVIII Airbome Corps and
Ft. Bragg 28307
ATTN: AFZA-DEH-EE

Chanute AFB, IL 61868
3345 CES/DE, Stop 27

NAVFAC
ATTN: Facilities Engr Cmd (9)
ATTN: Naval Civil Engr Lab (3)

Engineering Societies Library
New York, NY 10017

U.S. Naval Oceanographic Office (2)
ATTN: OAAD
Stennis Space Center, MS 39522

ITD SRSC
Stennis Space Center, MS 39529

Dept of Environmental Rsrcs
New Brunswick, NJ 08903

School of Civil Engineering
West Lafayette, IN 47907

National Cartographic Center
Cartography & Geographic Information Systems
Div.
Washington, D.C. 20013

U.S. Dept of Commerce
Washington, DC 20233

NOAA
Boulder, CO 80303

U.S. Geological Survey
Reston, VA 22092

NASA
NSTL, MS 39529

NORDA
NSTL, MS 39529-5004

USGS, Branch of Geophysics
Denver, CO 80225

DBA Systems, Inc.
Fairfax, VA 22030

Technologies Services Group
Marietta, GA 30062

National Guard Bureau 20310
Installation Division

US Government Printing Office 22304
Receiving/Depository Section (2)

US Army Support Command, HI 96858

US Army Env. Hygiene Agency
ATTN: HSHB-ME 21010

Defense Technical Info. Center 22314
ATTN: DDA (2)

124
+10
03/90